

REST Parameter Object



This page explains the **REST Import Rules** in Bridge context. If you were looking for the same information regarding the [PAS Designer](#), refer to [OpenAPI Import Rules](#) in the Designer guide.

Parameter objects can be defined inline or be a reference to a parameter of the parameters list.

Element	Used By Importer	Description	More Information at ...
name	✓	The name of the parameter. Parameter names are case sensitive. - If in is "path", the name field must correspond to the associated path segment from the path. - For all other cases, the name corresponds to the parameter name based on the in property.	See Path Templating for further information.
in	✓	The location of the parameter. Possible values are "query", "header", "path" or "body". "formData" is not supported by the importer and ignored.	
description	✗	A brief description of the parameter	
required	✓	Determines whether this parameter is mandatory. If true, the multiplicity of the parameter is set to 1, else it is set to 0..1.	
schema	✓	If in is "body", schema defines the type used for the body parameter.	Schema Object
type	✓	if in is other than "body", type defines the type of the parameter. integer: the base type Integer is used. number: the base type Float is used. boolean: the base type Boolean is used. string: the type depends on the format. - byte: the base type Blob is used. - date-time: the base type DateTime is used. - otherwise the base type String is used. array: the parameter will be an <<E2EArray>> and the class of items is used as arrayElement. If type is not given at all, and the definition has no properties, it will be imported as <code>urn:BaseTypes:Any</code>.	
format	✓	The format of the object is used to be more specific when the type is string.	
items	✓	The item is a schema object to define the type of element in the array. Only used if type is array.	Schema Object