Uploading Log Files



The **Log File Queue** menu allows you to monitor the log file import from your services to Process Mining.

In section **Log File Upload** you can also upload log files manually.

You have to other options in the **Log File Queue** menu:

Related Pages:

- Administrating Process Mining
  - Collecting Logs
  - Adding Diagrams
  - Setting a Retention Time for Instance Data
  - Using Calculated Metrics
  - Monitoring the ETL Process State
  - Monitoring the Log File Queue

Related Documentation:

- Process Mining Installation Guide
- Process Mining
- BRIDGE Integration Platform User's Guide
  - Transaction Log Levels of an xUML Service

- Go to page Monitoring the ETL Process State to learn more about the state of the ETL service.

- Go to page Monitoring the Log File Queue ue for further information about the contents of the log file queue.



If you want to upload log files manually, go to section **Log File Upload**. This section enables the subsequent upload of old log files, for example if a new system has been set up and you want to use older data then the log files created in the new system.

First you have to specify the meta data for the upload:

- **Service:** Insert the name of the service that provided the data.
- **Host:** Insert the name of the host on which the service was running from which the log data originates.
- **Port:** Insert the number of the service port.
- **Log Level:** Select the desired log level. Your options are **Custom**, **Service** and **IO**.

Refer to Bridge Guide > Transaction Log Levels of an xUML Service for detailed explanations of the different log levels.



Only when you have entered the meta data completely, the upload field is displayed.

You have two options to upload the import file:

1. Use drag and drop to place your document to the space marked **Drop file here**.
2. Click the **Upload File** button to select your file.

> The supported format is .zip. Make sure that the zip file contains only the .log files to be imported without any directory structure. The structure in the original files can be in .csv or .json format.

Once the file has been dropped, the upload starts automatically.