

IDoc Import Rules

IDocs (Interface **D**ocuments) are the most common way of interchanging data asynchronously with SAP R/3. IDocs consists of control and data records. The control record contains data like IDoc type, sender, receiver, IDoc number and many others. Its purpose is to control the routing and handling of the IDoc. The data records are called segments. Each segment has an 63 byte long header and a 1000 byte data part.

The most simple IDoc is TXTRAW01 containing as data part just a string. The IDoc header contains information like segment type, segment number, parent number, and so forth. The parent number is used to link the segment to other segments building a hierarchical structure. The data part consists of values put in position dependent slots. The information which data attribute is found on which position can be found in the IDoc parse grammar (**WE60** - choose IDoc type - click on **Parser (F9)**) on your SAP system. More information about IDocs can be found in the SAP Library help. The result of importing TXTRAW01 together with the description of the SAP parser grammar to UML mapping is shown in the class diagram TXTRAW (see [figure "Example Of an Imported TXTRAW IDoc"](#)).

The modeler must execute the following steps in order to get UML classes of a SAP IDoc:

1. Generate the parse grammar.
2. Generate a WSDL file from the generated SAP IDoc parse grammar.
3. Import the generated WSDL into the UML model.
You can find more information of how to execute this step on [Importing SAP IDoc Meta Data](#) the E2E Builder User's Guide.
4. Model and compile the IDoc transformations.
You can find more information of how to execute this step on [IDoc Handling](#).

Structure of the Imported Classes

The result of importing SAP IDoc parse grammars will be a set of classes being of stereotype `<<SAPIDoc>>`. Such classes must be derived from the EDI_DC40 class which holds all attributes found in the control record because the control record is common to all IDocs (see [figure "Example Of an Imported TXTRAW IDoc"](#)). Each segment is modeled as class of stereotype `<<SAPIDocSegment>>` that has an association to the IDoc class or to other segments. The association end name and multiplicity is given by the segment name respectively the LOOPMIN/LOOPMAX numbers in the SAP parse grammar.

An example of a SAP IDoc parse grammar is:

```
BEGIN_SEGMENT_SECTION
  BEGIN_IDOC      TXTRAW01
    BEGIN_SEGMENT E2TXTRW
      SEGMENTTYPE E1TXTRW
      LEVEL       02
      STATUS      MANDATORY
      LOOPMIN     0000000001
      LOOPMAX     0000003600
    BEGIN_FIELDS
      NAME        TLINE
      TEXT        Text line for SAPmail via IDoc interface
      TYPE        CHARACTER
      LENGTH      000072
      FIELD_POS   0001
      BYTE_FIRST  000064
      BYTE_LAST   000135
    END_FIELDS
  END_SEGMENT
END_IDOC
END_SEGMENT_SECTION
```

If segment STATUS is MANDATORY and if LOOPMIN is 0, the lower multiplicity is set to 1 to be consistent.

SAP IDoc segment classes have the following tagged values:

Tagged Value	Description
--------------	-------------

On this Page:

- [Structure of the Imported Classes](#)
- [Generating and Importing Meta-information](#)

Related Pages:

- [Importing SAP IDoc Meta Data](#)
- [IDoc Handling](#)

hierarchy Level	corresponds to <code>LEVEL</code> in the SAP parse grammar.
type	corresponds to <code>SEGMENTTYPE</code> in the SAP parse grammar
group	Segments containing child segments (see class diagram of <code>CREMAS01</code> , figure "Fragmentary View of CREMAS01 IDoc Class Structure") are called group-segments. These segments and its children are nested within a <code>BEGIN_GROUP</code> section in the SAP parser grammar. The <code>BEGIN_GROUP</code> tag is associated with a number which is put into the group tagged value for each group-segment.

Segment attributes can have the following tagged values:

Tagged Value	Description
order	gives the order of the attribute within the IDoc; corresponds to <code>FIELD_POS</code> in the SAP parse grammar
offset	index position in bytes starting at the beginning of the segment; corresponds to <code>BYTE_FIRST</code> in the SAP parse grammar
externalLength	reserved length of the field in the IDoc segment: <code>BYTE_LAST - BYTE_FIRST</code>
internalLength	length in the SAP system: corresponds to <code>LENGTH</code> in the parse grammar
nativeType	basic data type of the segment attribute. The supported types are listed beneath
decimals	number of decimals. Relevant only for numeric types such as <code>DEC</code>

Figure: Example Of an Imported TXTRAW IDoc

