



e2ebridge.e2e.ch

Preferences | Logging | Runtime | Certificate

### System Information

Scheer PAS BRIDGE	7.5.1 [linux-64]
Operating System	Linux 3.10.0-862.14.4.el7.x86_64

### Runtime Components

xUML Runtime	2019.6 [BASE,SAPNW]
Node.js	8.16.0
Apache Proxy	2.4.39
Java Runtime Environment	11.0.3 [amd64] [UTF-8]

## Changing the Preferences of the Java Adapter

In a browser, open the Web-based user interface of the BRIDGE of the system, on which the Bridge is installed (see [Checking the Installation](#)). Enter a user id and password of a user with administration rights (the predefined user **admin**, for instance). The welcome page is displayed.

In the Navigation, select the Bridge item of the node instance you want to define the Java preferences for (in this example **e2ebridge.e2e.ch**) and switch to tab **Preferences**. In the drop down list, select the **Java Adapter**.

**i** After installation of the BRIDGE, the Java Virtual Machine that is used by the Bridge is initially defined.

You may now change the Java Home directory.

Key	Value
-----	-------

JAVA_HOME	Path to the Java Runtime, e.g. <b>C:\E2E_BRIDGE_PROG\j2re-11.0.3\win32-64</b>  <b>Linux: /opt/e2e_bridge_prog/j2re-11.0.3/linux-64</b>
-----------	---



We strongly recommend to use no Java Runtime older than the one that has been installed with the BRIDGE. This ensures that deployed xUML services will run properly.

Using Windows, you can copy the path from Windows Explorer (default directory **C:\E2E\_BRIDGE\_PROG\j2re-x.x.x\win32-64**).