

# Options: Deploy Bridge Repository

Using this option you can overwrite the preferences of all [Deploy test actions](#) test actions.

Test Preferences

Edit test action preferences and compare functions

Repository File

...

Host

Port

Username

Password

☒ Override existing

☐ Should not exist

☐ Override settings

☒ Keep changed settings

☐ Start service

☒ Do not start service

Logfile

...

OK

Cancel

Related Pages:

- [Options: Build Bridge Repository](#)
- [Options: Compare the Result of a Bridge Request](#)
- [Options: Compare two XML Documents](#)
- [Options: Deploy Bridge Repository](#)
- [Options: Send a Request to a Bridge](#)
- [Options: Start/Stop Bridge Service](#)
- [Options: Wait for a Specific Time Interval](#)

In general, all options can be overwritten. Clear all fields whom you want to keep the value defined in the test action, and enter values in the fields only that you want to overwrite.

Preference	Description
Repository File	Overwrite name and path of the UML model you want to build the repository of.
Host	Overwrite the name of the Bridge, you want to deploy the service to.
Port	Overwrite the Bridge port.
Username /Password	Overwrite a valid username and password to access the Bridge.
Deploy options	Overwrite the deployment options. For more information on deployment options, refer to <a href="#">Deployment of xUML Services</a> .
Logfile	Overwrite name and path of the logfile. The logfile will be used for compare tests.