Managing Test Cases

The following operations can be executed on test cases via the context menu to manage test cases:

Function	Description
Run test case	Select Run Test Case to send out a SOAP request.
Clear test case	 Select Clear Test Case to clear all SOAP messages. The following tabs are cleared: Response UML Request log Response log The Input data on the Request tab remains untouched.
Duplicate test case	By selecting Duplicate Test Case you can create a copy of the selected test case, including the input data specified on the Request tab. You will be prompted to enter the name of the new test case. Y Copy Test Case Enter the name of the new test case. Test Case Name with keywords1 OK Cancel
Copy & Paste test case	Using Copy & Paste on a test case has the same effect as using Duplicate Test Case. Additionally, you can not only create a duplicate of the test case below the very same SOAP operation, but you can paste the test case to another operation or even to a SOAP operation of another WSDL definition. Be aware of what you are doing, though. The Trace Analyzer will warn you, that copying a test case to a different WSDL or location may result in runtime errors.
Rename test case	Use Rename Test Case to change the name of a test case.

Related Pages:

- Creating Test Cases
 Importing the Service Description

Delete test case	Use Delete Test Case (or select the test case and press Del) to erase the specified test case, including stored input and output data, and all SOAP messages. Y Question × Delete Test Case 'with keywords'? ?
	Are you sure to delete the test case 'with keywords'?
	Yes No
Properties	Select Properties to view and edit the test case properties. Properties is the default menu entry and can be accessed by double-clicking the test case.