

xUML Service Stop Log

A stop log will be created, if the service could not be stopped regularly but if errors occurred upon stopping. The stop log contains the following information:

- information about the selected xUML service
 - working directory of the xUML service
 - system information
 - and more ...
- errors that occurred during the shutdown of the xUML service

Select **stop** from the **Type** dropdown list. Selecting a date has no effect, as the stop log will be overwritten each time the xUML service is stopped.

SupportManager

[xUML Service](#)[Documentation](#)[History](#)[Logging](#)[Dump](#)[Settings](#)[Version](#)[Persistent State](#)[Status](#)

xUML Service Logs

typestop

log level

from2018-10-05 10:08:00to

ViewDownload

☐ Auto Refresh in 60 sec.

Show20entries

=====

/opt/docu/e2ebridge/e2e_bridge_data/bridge_SupportManager

PLATFORM = linux-64

PATH = /sbin:/usr/sbin:/bin:/usr/bin

CONSOLE_HOME = /opt/docu/e2ebridge/e2e_bridge_prog

BRIDGESERVER_BIN = /opt/docu/e2ebridge/e2e_bridge_prog/bridgeserver-2018.12/linux-64

INSTANCE_HOME = /opt/docu/e2ebridge/e2e_bridge_data/bridge_SupportManager

=====

Killed process 4886

Showing 1 to 11 of 11 entries

Previous1Next

How to search the logfiles is explained in detail on [Logging of xUML Services](#).