Label

Element	FormLabel
lcon	
Description	Use the label field to design headers in your form.
Туре	n/a
Prepopulation	This element cannot be prepopulated.
Editing	Refer to Modeling Forms for further information regarding editing of form elements using the context menu.

Configuration Options

 \odot

Use the Attributes panel to edit the form element.

Attribute	Description	A	llowed Values
Name	Technical identifier for data processing and not visible for the end user.	cha	hanumercial aracters and derscore. It is not allowed to start the name with a number.
Description	A commentary field for the developer. The content is invisible to users and its sole purpose is internal documentation.	An	y string.
Label	Field name shown in the form.	Ang	y string.
Style	Click O to open a new window for editing. You can find more information under Sytle Editor.	An	y string.
Vertical Alignment	The attribute is used to adjust the position of a form element in context to a bigger neighboring element.	Т ор	Align the element or top of the element cell (default).
	Example: The Radio Button Group Color is much bigger than the Butt on Next, but the button should be shown at the bottom of the form. Therefore, the button's attribute Vertical Alignment is set to Bottom.	C e nt er	Align the element in the middle of the element cell.
	Color Blue Green Red	B ot tom	Align the element at the bottom of the element cell.
	Vellow Next		
CSS Class	Enables a field-acurate layout customization.	Av	alid CSS class.

On this Page:	
• Config	guration Options Style Editor
Simple_Form	n_Example
↓	Click the icon to download a simple example model that shows how you can confi gure form elements in Sche er PAS Designer.

Related Pages:

Supported Form Elements

Custom Attributes	The attribute is used to activate Angular directives, that are created as development kit (devkit) library to expand the default functionality.	 empty attribute attribute with value
	For detailed information about Angular directives, visit the of ficial Angular documentation. For details about the usage of the Custom Attributes , refer to Developing Custom Directives.	(e.g. color="red") • multiple entries separated by space (e.g. color=" red" multiline max=" 5")
Symbol Type	Displays the type of the form element in read-only mode.	_

Style Editor

In the **Preview** area you can format the text.

Preview	w Text Style						
	Test Label						
Format Default	Ŧ	Fort Family Default	•	Font Size Default	Ŧ	BIU	properties.
						Save	Cancel

You can edit:

Option	Description
Format Default	Use this option to change the Text Format . Available values are: • Default • Paragraph • Header 1, 2, 3, 4, 5, 6
Font Family Default	 Guote Quote Use option Font Family to change the font type of your text. Available values are: Default Arial Arial Black
Font Size Default	Use this option to change the Font Size . Available values are: • Default • 8px • 9px •
ΒΙΨ	Use these buttons to format your text: Bold (not available for header formats) Italic Underline
	Use these buttons to change the text alignment: Left Center Right

Save Use the Save button to save your changes. Cancel Use the Cancel button to discard your changes.		Use this option to change the font color. Click on the box to open the color picker:
Cancel Use the Cancel button to discard your changes.	Save	Use the Save button to save your changes.
Canoci	Cancel	Use the Cancel button to discard your changes.