

POP3

Tagged Values (<<POP3Alias>>)

Tagged Value	Description	Allowed Values
host	POP3 host.	A valid hostname.
port	POP3 port.	A valid port number.
user	Username/password.	

On this Page:

- [Tagged Values \(<<POP3Alias>>\)](#)
- [POP3 Adapter Parameters](#)
- [POP3 Adapter Parameter Types](#)

POP3 Adapter Parameters

Name	Type	Direction	Description
server	String	in	Specify the POP3 server.
port	Integer	in	Specify the POP3 port.
authentication	POP3Authentication	in	Use this parameter to provide the POP3 username and password.
deleteOnServer	Boolean	in	Specify whether messages that have been read should be deleted on the server.
sessionId	String	out	This parameter returns the POP3 session ID.
message	POP3Message	out	This parameter returns a POP3 message.

POP3 Adapter Parameter Types

Class	Attribute	Type	Description
POP3Authentication	username	String	Username for authentication.
	password	String	Password for authentication.
POP3Message	content	Blob	POP3 message content.
	sender	String	POP3 message sender.
	recipient	String	POP3 message recipient.
	date	DateTime	POP3 message date.
	subject	String	POP3 message subject.
	id	String	POP3 message id.
	headerParameters	MIMEHeaderField	POP3 message header parameters.
	header	Blob	POP3 message header.
MIMEHeaderField	name	String	Name of the MIME header.
	value	String	Value of the MIME header.